

# BUILD MAN

BuildMan  
Grade

# SCAFFOLDING AND DRYWALL TRADES




# METALTECH

BUILT TOUGH FOR  
SAFETY



# 6' BUILDMAN™ DRYWALL BAKER SCAFFOLD

**NEW WITH**  
**SAFECLIMB™**  
**PLATFORM**



**SAFECLIMB TRAPDOOR  
AND ANTI-SLIP DECK**



**TIGHTENING HANDLE  
FOR MORE STABILITY**

**EACH END CAN ADJUST  
SEPARATELY TO BE USED  
ON BOTH LEVEL SURFACES  
AND STAIRWAYS**



**SAFECLIMB RUNG STEP**



**QUICK AND EASY HEIGHT  
ADJUSTMENT**



## TECHNICAL FEATURES

ASSEMBLED DIMENSIONS (WxDxH)	75 3/4 X 31 X 76 IN. (192.4 X 78.7 X 193 CM)
WEIGHT	165 LB (74.8 KG)
LOAD CAPACITY	1,500 LB (680 KG) COMBINED WEIGHT OF USER + MATERIALS
WORKING HEIGHTS	FROM 29 TO 71 1/2 IN. (73.7 TO 181.6 CM), 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS
REACH	12 FT (3.7 M), STACKABLE UP TO 3 UNITS HIGH FOR 24 FT (7.4 M) REACH
DECK (WxD)	29 X 67 IN. (73.7 X 170.2 CM) PLATFORM WITH TRAPDOOR, 19/32 IN. (15 MM) PLYWOOD, SLIP-RESISTANT
BRACE	DOUBLE LOCKING STEM MECHANISMS WITH TIGHTENING KNOBS TO PREVENT LOOSENESS IN THE STRUCTURE
CASTERS	6 IN. (15 CM) DOUBLE LOCKING HEAVY DUTY
MODEL	I-BMSS
UPC	778300100057

\* All trademarks and registered trademarks listed above are the property of their respective owners.

**12'** REACH

**1,500 lb** LOAD CAPACITY



ANTI-SLIP DECK



TRAPDOOR ACCESS



NON-MARKING



STACKABLE

**OSHA  
ANSI  
CSA**

# ACCESSORIES

## FOR 6' BUILDMAN™ DRYWALL BAKER SCAFFOLD



### CLIMB-N-GO MOTORIZED SYSTEM FOR BAKER TYPE SCAFFOLD

MODEL: I-CNG  
UPC: 778300006083



### GUARDRAILS SYSTEM

MODEL: I-BMSGRJP  
UPC: 778300001828



### SET OF 14 IN. OUTRIGGERS WITH CASTERS FOR 2 UNITS HIGH

MODEL: I-BMS04  
UPC: 778300100262



### SET OF 46 IN. OUTRIGGERS WITH CASTERS FOR 3 UNITS HIGH

MODEL: I-BMS04TT  
UPC: 778300003792



### 39 IN. HIGH EXTENSION

MODEL: I-BMSSEX  
UPC: 778300001323



SCAFFL©/CK

### SAFETY BRAKES

MODEL: I-ISL  
UPC: 778300001552



### SET OF 4 BASE PLATES

MODEL: I-IBBF4  
UPC: 778300001699



### SET OF 4 LEVELING JACKS

MODEL: I-IBSJP12H4  
UPC: 778300001644

### GUARDRAILS SYSTEM

### 3 UNITS TOWER 24 FT REACH

17.5'

### 46 IN. OUTRIGGERS

